

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	6th Annual Summer Sizzler 2024				
TRACK	Soda City Raceway				
NAME	Kyle Rumble		DATE	June 9, 2024	
QUAL POSITION	3	FINAL POSITION	1	BEST LAPTIME	7.6 /sec
LAPS	39 / 5:06				

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	27 /T	SPUR GEAR
	110 /T	FINAL DRIVE RATIO

FRONT	SHOCKS	REAR
2.4-2.7	XRAY SPRINGS	2.8
400	OIL /Cst	400
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO

<input type="checkbox"/> 4 HOLES	1.1mm	1.1mm	<input type="checkbox"/> 4 HOLES
<input checked="" type="checkbox"/> PSS	1.2mm	1.2mm	<input checked="" type="checkbox"/> PSS
SHOCK LENGTH	/mm	/mm	SHOCK LENGTH
1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm
			1.2

Gravity	TIRES	Gravity
SXT 3.0	ADDITIVE	SXT 3.0
6 mins	ADDITIVE TIMING	6 mins
5 mins	WIPE OFF TIME	5 mins
Timing:	TIRE WARMERS	Timing:
FRONT LEFT		REAR LEFT
FRONT RIGHT		REAR RIGHT
TREATED AREA		

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT	%	REAR	%
MOTOR	Orca Modtreme 5.0	TIMING	34			
ESC	Orca OE1 Mk2	BATTERIES	Orca 4290mah			
BODY	Twister	WING	Speciale			

69 /mm	Dimension from body post to window bottom line	BODY POSITION
7 +2 holder	Dimension from body post to upper holder	WING SIDE PLATE
	Dimension from edge to surface	

X4'23	<input checked="" type="checkbox"/> 1.6mm	<input checked="" type="checkbox"/> 2.0mm	<input checked="" type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm
X4'22	<input type="checkbox"/> 2.0mm	<input type="checkbox"/> 1.6mm	<input type="checkbox"/> NONE
	<input type="checkbox"/> BEARING		

COMMENTS

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	HEIGHT
1.75 /mm	/mm
SHIM	SHIM
4 /mm	/mm
TOE GAIN	TOE GAIN
2.0 /mm	2.0 /mm
FRIDE HEIGHT	FRIDE HEIGHT
5.0 /mm	5.2 /mm
RRIDE HEIGHT	RRIDE HEIGHT
2.0 /mm	2.5 /mm
SERVO SAVER	SERVO SAVER
SERVO HORN	SERVO HORN

FRONT
2 /deg. CAMBER
Left = Right
BODY STOP
YES <input checked="" type="checkbox"/> NO
SHOCK HOLDERS
SHIM 2.5 /mm
SUSPENSION FLEX
YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT
58mm 59mm
BEARING BLADE
#107702 Chassis Droop Gauge Blocks
#107712 Chassis Droop Gauge
5.6 /mm
DOWNSTOP

REAR
2 /deg. CAMBER
Left = Right
BODY POST
VERTICAL
HORIZONTAL <input checked="" type="checkbox"/>
SHOCK HOLDERS
FIXED <input checked="" type="checkbox"/> ACTIVE
SHIM 4 /mm
SUSPENSION FLEX
YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT
52mm 54mm
BEARING BLADE
#107702 Chassis Droop Gauge Blocks
#107712 Chassis Droop Gauge
4.8 /mm
DOWNSTOP

FRONT TOP VIEW	REAR
1 TOE OUT	2.75 TOE IN
Left = Right	Left = Right
ACKERMANN	SHORT LiPo BRASS WEIGHT
SHIM 1.0 /mm	YES <input checked="" type="checkbox"/> NO
BRASS WEIGHT FOR MOTOR MOUNT	YES <input checked="" type="checkbox"/> NO
DIFF POSITION	DIFF POSITION
<input type="checkbox"/> UP	<input checked="" type="checkbox"/> UP
<input checked="" type="checkbox"/> DOWN	<input type="checkbox"/> DOWN
<input type="checkbox"/> +1mm	<input type="checkbox"/> +1mm
UPPER ARM	UPPER ARM
SOFT	SOFT
MEDIUM <input checked="" type="checkbox"/>	MEDIUM
STEERING BRIDGE	STEERING
YES <input type="checkbox"/> NO	SHIM /mm
HUB OFFSET	PLATE
STD. <input checked="" type="checkbox"/> -0.5mm	8.0mm 7.5mm
+0.5mm	STD.
SHIM /mm	

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
/deg.	ALU BRASS
MOTOR MOUNT	CHASSIS T-BRACE
SERVO HOLDER	
FR RE	
FRONT ARMS	REAR ARMS
MEDIUM	MEDIUM
HARD <input checked="" type="checkbox"/>	HARD <input checked="" type="checkbox"/>
CHASSIS	
GRAPHITE	
ALU	
ALU 1.5mm <input checked="" type="checkbox"/>	