

RACE	EC Roeselare Belgium 2024				
TRACK	RCR Roeselare				
NAME	Jacques Libar		DATE	25.08.2024	

TRACK TEMP.	QUAL POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
	6	5	19.1 /sec	/ /	/

TRACK

TRACK SURFACE	<input type="checkbox"/> CARPET	<input checked="" type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED <input checked="" type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL		200K /cSt
PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
38	90	4.5

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /Cst	350
	REBOUND %	

☒ 4 HOLES
☐ PSS

☒ 1.1mm
☐ 1.2mm

☒ 1.1mm
☐ 1.2mm

SHOCK LENGTH

8.5 /mm

8.5 /mm

SHOCK LENGTH

ANTI-ROLL BAR

1.4	THICKNESS/mm	1.6
-----	--------------	-----

RIDE	TIRES	
TriStar	ADDITIVE	
20 min	ADDITIVE TIMING	
5	WIPE OFF TIME	
Timing:	Temp.: 65	Timing: Temp.:
FRONT LEFT	FRONT RIGHT	REAR LEFT REAR RIGHT
TREATED AREA		

TOTAL WEIGHT	1261 /g	WEIGHT BALANCE
		FRONT 67 % REAR 33 %
MOTOR	21.5	TIMING
ESC	Team Zombie	BATTERIES
BODY	Blitz YRS	WING
		Nosram 4900
		std

BODY POSITION

WING SIDE PLATE ☒ YES ☐ NO

Dimension from edge to surface

BODY POSITION

WING SIDE PLATE ☒ YES ☐ NO

Dimension from edge to surface

BODY POSITION

WING SIDE PLATE ☒ YES ☐ NO

Dimension from edge to surface

FRONT & REAR SUSPENSION

FRONT CASTER

☐ 5° ☒ 4° ☐ 3°

Adjust with eccentric bushings

BUMP STEER
0.5 /mm

HEIGHT
19 /mm

SHIM
4 /mm

FF 2.0 /mm ☒ **RIDE HEIGHT** 5.0 /mm ☐

FR 2.0 /mm ☒ **SERVO SAVER** ☐ **SERVO HORN** ☒

REAR CASTER

☐ 0.5° ☒ 1.5° ☐ 2.5° ☐ 3.5° ☐ 4.5° ☐ 5.5°

Adjust with eccentric bushings

TOE GAIN 5 /mm

RF 2.0 /mm ☒ **RIDE HEIGHT** 5.2 /mm ☐

RR 2.0 /mm ☒

FRONT SUSPENSION

CAMBER 2.0 /deg. Left = Right

BODY STOP YES ☒ NO ☐ /mm

SHOCK HOLDERS SHIM 2 /mm

SUSPENSION FLEX YES ☒ NO ☐

DRIVE SHAFT 58mm ☐ 59mm ☒ BEARING ☒ BLADE ☐

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 5.6 /mm DOWNSTOP

REAR SUSPENSION

CAMBER 2.0 /deg. Left = Right

SHOCK HOLDERS FIXED ☒ ACTIVE ☐ SHIM 2 /mm

SUSPENSION FLEX YES ☒ NO ☐

#107702 Chassis Droop Gauge Blocks #107712 Chassis Droop Gauge 4.6 /mm DOWNSTOP

FRONT HUB

MEDIUM ☐ HARD ☒ GRAPHITE ☐ ALU ☐

SHIM 0.5 /mm

REAR HUB

MEDIUM ☐ HARD ☒ GRAPHITE ☐ ALU ☐

SHIM 1.0 /mm

FRONT TOP VIEW

TOE OUT 1 Left = Right

DIFF POSITION UP ☒ +1mm ☐ STD. ☐ DOWN ☐

UPPER ARM COMPOSITE ☒ EXTRA SOFT ☐ SOFT ☐ MEDIUM ☐

HUB OFFSET STD. ☒ -0.5mm ☐ +0.5mm SHIM/mm

REAR TOP VIEW

TOE IN 2.5 Left = Right

ARS LINKS SHIMS 5 /mm

UPPER ARM COMPOSITE ☒ EXTRA SOFT ☐ SOFT ☐ MEDIUM ☐

HUB OFFSET STD. ☒ -0.5mm ☐ +0.5mm SHIM/mm

FRONT BOTTOM VIEW

WEIGHT LEFT & RIGHT #309826 YES ☐ NO ☒ 50g + 50g

BUMPER WEIGHT 100g YES ☒ NO ☐

FRONT ARMS MEDIUM ☐ HARD ☒

REAR BOTTOM VIEW

STEER. LOCK 26 /deg.

T-BRACE ALU ☐ BRASS ☐

CHASSIS GRAPHITE ☐ ALU ☐

REAR ARMS MEDIUM ☐ HARD ☒