

SET-UP SHEET

X4F'25 SET-UP SHEET VER.1 ©XRAY

XRAY X4F'25

RACE	Hasloh		
TRACK	Megadrom		
NAME	Thorsten Heins	DATE	16.11.2024

TRACK TEMP.	QUAL. POS.	FINAL POS.	BEST LAPTIME	LAPS	TIME
14			13.7 /sec	21 /	5.08

TRACK			
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT	
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFFERENTIAL - OIL 300K /cSt		
PINION / T	SPUR GEAR / T	FINAL DRIVE RATIO
38	100	5.0

FRONT	SHOCKS	REAR
2.5-2.8	XRAY SPRINGS	2.6
350	OIL /cSt	350
-	REBOUND %	-

<input checked="" type="checkbox"/> 4 HOLES	<input checked="" type="checkbox"/> 1.1mm	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	<input type="checkbox"/> 1.2mm	1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH	8.5 /mm	9.0 /mm	SHOCK LENGTH

1.3	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.8
-----	--------------	---------------	--------------	-----

Ride ETS	TIRES ADDITIVE ADDITIVE TIMING WIPE OFF TIME TIRE WARMERS	Ride ETS
MR33 V4		MR33 V4
10 min		10 min
Timing:		Temp.:

FRONT LEFT	FRONT RIGHT	TREATED AREA	REAR LEFT	REAR RIGHT

TOTAL WEIGHT	/g	WEIGHT BALANCE	FRONT	%	REAR	%
--------------	----	----------------	-------	---	------	---

MOTOR	HW ETS	TIMING	RPM LIMIT	17500
ESC	HW ETS	BATTERIES	Intellect 4400 MC3	
BODY	YRS	WING	Std.	

<p>Dimension from body post to window bottom line</p> <p>WING SIDE PLATE YES <input checked="" type="checkbox"/> NO <input type="checkbox"/></p> <p>Dimension from body post to upper holder</p> <p>Dimension from edge to surface</p>	BODY POSITION
--	----------------------

<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
TOP DECK CUTTING							

nochmal testen
Shocks Front PSS
Springs Front 2.4-2.7
Diff 500K

FRONT CASTER	FRONT & REAR SUSPENSION			REAR CASTER
Adjust with eccentric bushings	BUMP STEER	HEIGHT	SHIM	Adjust with eccentric bushings
5° 4° 3°	1 /mm	19 /mm	7 /mm	0.5° 1.5° 2.5° 3.5° 4.5° 5.5°
2 /mm FF	5.0 /mm	FR 2 /mm	<input type="checkbox"/> SERVO SAVER	TOE GAIN 5 /mm
			<input checked="" type="checkbox"/> SERVO HORN	