

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	X4 25- 180 Club Race - 21.5				
TRACK	180 Raceway				
NAME	Mike Gee	DATE	11/16/24		
QUAL POSITION	1	FINAL POSITION	1	BEST LAPTIME	/sec
LAPS	/				

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input checked="" type="checkbox"/> TECHNICAL	<input type="checkbox"/> MIXED <input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW <input type="checkbox"/> MEDIUM	<input checked="" type="checkbox"/> HIGH

FRONT		TRANSMISSION		REAR	
GEAR DIFF OIL	/cst	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL	8000	/cst
PINION	/T	SPUR GEAR	90	FINAL DRIVE RATIO	

FRONT		SHOCKS		REAR	
2.6	XRAY SPRINGS	2.6			
550	OIL /Cst	550			
0	REBOUND %	0			
<input type="checkbox"/> YES <input type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input type="checkbox"/> NO			

<input type="checkbox"/> 4 HOLES	1.1mm	1.1mm	<input type="checkbox"/> 4 HOLES
<input checked="" type="checkbox"/> PSS	1.2mm	1.2mm	<input checked="" type="checkbox"/> PSS
SHOCK LENGTH			
7.5	/mm	7.5	/mm

1.2	THICKNESS/mm	ANTI-ROLL BAR	THICKNESS/mm	1.2
-----	--------------	---------------	--------------	-----

Gravity		TIRES	
SXT		ADDITIVE	
5		ADDITIVE TIMING	
		WIPE OFF TIME	
Timing:		Temp.:	
FRONT LEFT	FRONT RIGHT	REAR LEFT	REAR RIGHT
TREATED AREA			

TOTAL WEIGHT	1325	WEIGHT BALANCE	FRONT 51 % REAR 49 %
--------------	------	----------------	----------------------

MOTOR	Orca B3 21.5	TIMING	Blinky
ESC	Orca OE1 MK2	BATTERIES	PCR 5900
BODY	Wolverine 0.4	WING	Speciale UL

BODY POSITION	
Dimension from body post to window bottom line	
7+1	WING SIDE PLATE
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	
Dimension from edge to surface	

TOP DECK CUTTING	
1.6mm	<input checked="" type="checkbox"/> 2.0mm
2.0mm	<input type="checkbox"/> 1.6mm
NONE	<input type="checkbox"/> BEARING

COMMENTS

FRONT & REAR SUSPENSION	
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
5° 4° 3°	0.5° 1.5° 2.5° 3.5° 4.5° 5.5°
BUMP STEER	SHIM
2.5 /mm	3 /mm
TOE GAIN	TOE IN
2.0 /mm	2.0 /mm
FRIDE HEIGHT	RRIDE HEIGHT
5.2 /mm	5.4 /mm
FR 1.5 /mm	RR 2.0 /mm
<input checked="" type="checkbox"/> SERVO SAVER	<input checked="" type="checkbox"/> SERVO HORN

FRONT	
1.5 /mm	CAMBER
Left = Right	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BODY STOP
SHOCK HOLDERS	SHIM 1.5 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	58mm 59mm BEARING BLADE
FRONT HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM 1 /mm	
DOWNSTOP	5.8 /mm

REAR	
2 /mm	CAMBER
Left = Right	
YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>	BODY POST
SHOCK HOLDERS	SHIM 2 /mm
SUSPENSION FLEX	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
DRIVE SHAFT	52mm 54mm BEARING BLADE
REAR HUB	MEDIUM <input type="checkbox"/> HARD <input type="checkbox"/> GRAPHITE <input checked="" type="checkbox"/> ALU <input type="checkbox"/>
SHIM 1 /mm	
DOWNSTOP	4.8 /mm

FRONT TOP VIEW		REAR	
1	TOE OUT	2.5	TOE IN
Left = Right		Left = Right	
ACKERMANN	SHIM 0.5 /mm	SHORT LiPo BRASS WEIGHT	YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>
BRASS WEIGHT FOR MOTOR MOUNT	12		
DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm	DIFF POSITION	<input checked="" type="checkbox"/> UP <input type="checkbox"/> DOWN <input type="checkbox"/> +1mm
UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>	UPPER ARM	SOFT <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/>
STEERING BRIDGE	YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>	STEERING	SHIM /mm
HUB OFFSET	STD. <input type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm	HUB OFFSET	STD. <input type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM /mm

FRONT BOTTOM VIEW		REAR	
STEER. LOCK	24 /deg.	T-BRACE	ALU <input type="checkbox"/> BRASS <input type="checkbox"/>
SERVO HOLDER	FR RE	CHASSIS T-BRACE	
FRONT ARMS	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>	REAR ARMS	MEDIUM <input type="checkbox"/> HARD <input checked="" type="checkbox"/>
CHASSIS	GRAPHITE <input type="checkbox"/> ALU <input type="checkbox"/> ALU 1.5mm <input checked="" type="checkbox"/>		