

SET-UP SHEET

X4'24 SET-UP SHEET VER.1 ©XRAY

XRAY X4'24

RACE	Trofeo Schumacher				
TRACK	Rc landia				
NAME	Filippo X4 25		DATE		
QUAL POSITION	FINAL POSITION	BEST LAPTIME	LAPS	TIME	
		/sec	/		

TRACK		
TRACK SURFACE	<input checked="" type="checkbox"/> CARPET	<input type="checkbox"/> ASPHALT
TRACK LAYOUT	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF OIL	<input checked="" type="checkbox"/> FRONT SOLID AXLE	GEAR DIFF OIL
PINION	SPUR GEAR	FINAL DRIVE RATIO
28 /T	110 /T	

FRONT	SHOCKS	REAR
2.5/2.8	XRAY SPRINGS	2.6
350	OIL /Cst	350
0	REBOUND %	0
<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO	FOAM INSERTS	<input type="checkbox"/> YES <input checked="" type="checkbox"/> NO
<input checked="" type="checkbox"/> 4 HOLES	1.1mm	<input checked="" type="checkbox"/> 4 HOLES
<input type="checkbox"/> PSS	1.2mm	<input type="checkbox"/> PSS
SHOCK LENGTH		SHOCK LENGTH
7 /mm		7 /mm
1.2	THICKNESS/mm	1.2

Hot race	TIRES
Hudy carpet	ADDITIVE
5	ADDITIVE TIMING
	WIPE OFF TIME
	TIRE WARMERS
Timing:	Temp.:
FRONT LEFT	FRONT RIGHT
REAR LEFT	REAR RIGHT
TREATED AREA	

TOTAL WEIGHT	1280 /g	WEIGHT BALANCE	FRONT 50 %	REAR 50 %
MOTOR	5T	TIMING	30	
ESC	G3	BATTERIES	Nosram	
BODY	Matrix twister	WING	Twister	

67 /mm	Dimension from body post to window bottom line	BODY POSITION
8	Dimension from body post to upper holder	WING SIDE PLATE
65 /mm	Dimension from edge to surface	

1.6mm	<input checked="" type="checkbox"/>	2.0mm	<input checked="" type="checkbox"/>	1.6mm
2.0mm	<input type="checkbox"/>	2.0mm	<input type="checkbox"/>	1.6mm
2.0mm	<input type="checkbox"/>	1.6mm	<input type="checkbox"/>	
NONE	<input type="checkbox"/>	BEARING	<input type="checkbox"/>	

Top deck frp	COMMENTS
--------------	----------

FRONT & REAR	SUSPENSION
FRONT CASTER	REAR CASTER
Adjust with eccentric bushings	Adjust with eccentric bushings
BUMP STEER	SHIM
3 /mm	6 /mm
HEIGHT	SHIM
19 /mm	6 /mm
FRIDE HEIGHT	FRIDE HEIGHT
2 /mm	2.5 /mm
5 /mm	5.2 /mm
FR 2 /mm	RR 2.5 /mm
SERVO SAVER	SERVO HORN
<input type="checkbox"/>	<input checked="" type="checkbox"/>
TOE GAIN	TOE GAIN
4 /mm	4 /mm

FRONT	SHOCK HOLDERS	SHOCK HOLDERS
2 /mm	SHIM	SHIM
2 /mm	4 /mm	4 /mm
CAMBER	SUSPENSION FLEX	SUSPENSION FLEX
2 /deg.	YES <input checked="" type="checkbox"/> NO	YES <input checked="" type="checkbox"/> NO
Left = Right	YES <input checked="" type="checkbox"/> NO	YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT	DRIVE SHAFT	DRIVE SHAFT
58mm 59mm BEARING BLADE	58mm 59mm BEARING BLADE	58mm 59mm BEARING BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	#107712 Chassis Droop Gauge
	4.8 /mm	4.8 /mm

REAR	SHOCK HOLDERS	SHOCK HOLDERS
1 /mm	SHIM	SHIM
2 /mm	4 /mm	4 /mm
CAMBER	SUSPENSION FLEX	SUSPENSION FLEX
2 /deg.	YES <input checked="" type="checkbox"/> NO	YES <input checked="" type="checkbox"/> NO
Left = Right	YES <input checked="" type="checkbox"/> NO	YES <input checked="" type="checkbox"/> NO
DRIVE SHAFT	DRIVE SHAFT	DRIVE SHAFT
52mm 54mm BEARING BLADE	52mm 54mm BEARING BLADE	52mm 54mm BEARING BLADE
#107702 Chassis Droop Gauge Blocks	#107712 Chassis Droop Gauge	#107712 Chassis Droop Gauge
	5.8 /mm	5.8 /mm

FRONT TOP VIEW	REAR
1.5	2.6
TOE OUT	TOE IN
Left = Right	Left = Right
ACKERMANN	ACKERMANN
SHIM	SHIM
1 /mm	1 /mm
SHORT LiPo BRASS WEIGHT	SHORT LiPo BRASS WEIGHT
YES <input checked="" type="checkbox"/> NO	YES <input checked="" type="checkbox"/> NO
BRASS WEIGHT FOR MOTOR MOUNT	BRASS WEIGHT FOR MOTOR MOUNT
40g	40g
DIFF POSITION	DIFF POSITION
<input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN	<input type="checkbox"/> UP <input checked="" type="checkbox"/> DOWN
UPPER ARM	UPPER ARM
SOFT MEDIUM Link	SOFT MEDIUM Link
STEERING BRIDGE	STEERING BRIDGE
YES <input type="checkbox"/> NO	YES <input type="checkbox"/> NO
HUB OFFSET	HUB OFFSET
STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm	STD. <input checked="" type="checkbox"/> -0.5mm <input type="checkbox"/> +0.5mm SHIM/mm

FRONT BOTTOM VIEW	REAR
STEER. LOCK	T-BRACE
26 /deg.	ALU BRASS
SERVO HOLDER	CHASSIS T-BRACE
FR RE	FR RE
MOTOR MOUNT	MOTOR MOUNT
CHASSIS	CHASSIS
GRAPHITE ALU 1.5mm	GRAPHITE ALU 1.5mm
FRONT ARMS	REAR ARMS
MEDIUM HARD G	MEDIUM HARD G